



Kitchen & Bath Eggshell Enamel with Microban

512XX

Product Description:	Product Specifications:
<p>Kitchen & Bath Eggshell Enamel with Microban is an extremely durable 100% acrylic latex eggshell finish developed to withstand the moist, humid conditions in bathrooms and kitchens. The anti-spatter formulation flows on easily, hides well and levels beautifully to provide the ultimate in durability and mildew resistance. Kitchen & Bath Eggshell Enamel with Microban can be applied to most surfaces in any area of homes, commercial or industrial buildings requiring maximum moisture and mildew resistance.</p> <p>Kitchen & Bath Eggshell Enamel contains Microban antimicrobial product protection. This unique additive will inhibit the growth of stain and odor causing bacteria; mold, mildew and other fungal growth on the dried paint film. Microban protection provides an added level of protection between cleanings, but does not take the place of normal cleaning and disinfecting procedures and will not protect users or others against food borne illness. Microban additives are E.P.A. registered for use in paint. For more information visit www.microban.com.</p>	<p>Type: 100% Acrylic Latex Exposure: Interior Specular Gloss: 14 @ 60° ± 4 Volume Solids: 39.5 % ± 2 Solids by Weight: 54.3 % ± 2 Vehicle: 68.3 % ± 2 Pigment: 31.7 % ± 2 Dry Film Thickness: 1.7 mils Viscosity @ 77 °F: 103 KU ± 5 Maximum VOC: 150 g/liter Flash Pt °F: Non-combustible Thinner: Water Clean Up: Soap & Water</p>
Recommended Use:	<p>Available Colors and Bases: White Pastel</p>
<p>Plaster, sheetrock, wallboard, concrete, masonry block, wood, primed metal, galvanized metal, acoustical surfaces.</p>	
Application:	<p>Available Package Sizes: Quart Gallon</p> <p>(Weight Per Gallon: 11.1 lbs. ± .5 lb)</p>
<p>WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.</p> <p>Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities with vinyl patching paste or an appropriate patching compound. Premium Kitchen & Bath Eggshell Enamel with Microban is self-priming over bare sheetrock, composition board, ceiling tile and concrete.</p> <p>New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed. Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper. Ferrous Metal - Clean, then prime with Larcoloid Rust Inhibiting Metal Primer Wood - Seal knots and stains with Wipe-Out, Wipe-Out Low Odor or Wipe-Out 100% Acrylic Stain Block Masonry Block - Apply one coat of Mason-Cote Block Filler 3751 if a denser surface is desired.</p>	
Architectural Specifications:	<p>Drying Times:</p> <p>To Touch: 1 hrs. To Handle: 8 hrs. To Recoat: 4 hrs. (@ 70-77 °F, 50% R.H.)</p>
<ul style="list-style-type: none"> ▪ Plaster, Wallboard, Sheetrock: 2 coats Kitchen & Bath Eggshell Enamel ▪ Concrete, Non-Porous Masonry: 2 coats Kitchen & Bath Eggshell Enamel ▪ Porous Masonry and Block: 1 coat Mason-Cote® Block Filler 3751 1 or 2 coats Kitchen & Bath Eggshell Enamel ▪ Ferrous Metal - Un-primed: 1 coat Larcoloid® Rust Inhibiting Metal Primer 21150 1 or 2 coats Kitchen & Bath Eggshell Enamel 	<p>Surface Spread Rate:</p> <p>Smooth: 350-400 s.f./gal. Porous: 250-300 s.f./gal. (Spray Application is 50% of above)</p>
Precautions:	<p>Tools and Equipment:</p> <p>Brush - Synthetic, Nylon or Polyester</p> <p>Roller - 3/8" Nap Synthetic Fiber</p> <p>Airless Spray - .017 to .019 Tip</p>
<p>Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.</p>	
Safety Information:	
<p>Keep out of reach of children. Do not take internally. Close container after each use.</p>	